

Fiber Free

AP/Spiralflex® Spiral Duct Liner

The first elastomeric duct liner specifically designed for spiral ducts. Lightweight and conformable, AP Spiralflex is engineered to provide simplified installation, safeguard IAQ, attenuate HVAC noise and reduce energy loss.



- 20% lighter than ducts that require a heavier, more costly inner metal lining. May reduce overall construction support costs
- Self-supporting and conformable, the flexible lightweight backing keeps insulation tight against the duct wall
- Microban® antimicrobial product protection inhibits the growth of mold and mildew in the insulation
- Good at attenuating airborne background noise from HVAC systems
- Meets ASTM E 84 25/50 flame and smoke, ASHRAE 90.1 – 2010, ASHRAE Standard 189.1, IECC 2012 and California Title 24

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

 armacell®



Microban antimicrobial product protection is limited to the product itself and is not designed to protect the users of these products from disease causing microorganisms, or as a substitute for normal cleaning and hygiene practices.*

Technical Data: AP Spiralflex™ Spiral Duct Liner

Description:

Black, conformable, elastomeric composite material in roll form for use as a thermal and acoustical duct liner in spiral ducts. (Not recommended for oval ducts.)

Specifications Compliance:

ASTM C 1534 ASTM E84	NFPA 90A, 90B NFPA 255	UL 181 UL 723
-------------------------	---------------------------	------------------

Approvals, Certifications, Compliances:

- GREENGUARD® Gold Certified.
- Made with EPA registered Microban® antimicrobial product protection.
- Manufactured without CFCs, HFCs, HCFCs, PBDEs, or Formaldehyde.
- All Armacell facilities in North America are ISO 9001:2008 certified.

Typical Properties

Specifications:	Values	Test Method:
	AP Spiralflex 1"	
Thermal Conductivity: Btu • in./h • ft ² • °F (W/mK)		
75°F Mean Temperature (24°C)	0.28 (0.040)	ASTM C 177 or C 518
90°F Mean Temperature (32°C)	0.286 (0.042)	
Flame Spread and Smoke Developed Index:	25/50 rated	ASTM E 84
Mold Growth: Fungi Resistance: Bacterial Resistance:	Passed	UL181 ASTM G21/C1338 ASTM G22
Upper Use Limit:	180°F (82°C)	ASTM C534
Lower Use Limit:	-297°F (-183°C)	ASTM C534
Erosion Resistance:	Does not break away, flake off or show evidence of delamination at velocities of 10,000 ft/min	ASTM C 1071
Corrosiveness:	Noncorrosive	ASTM C 665
Odor Emissions:	No objectionable odors	ASTM C 665

R-VALUE	R-4.2
	1"

Sizes: Wall Thickness	Roll Width
1" (nominal)	48"



ARMACELL LLC

TEL: 800.866.5638

FAX: 919.304.3847

info.us@armacell.com

www.armacell.us

7600 Oakwood Street Extension, Mebane, NC 27302



Armacell provides this information as a technical service. To the extent the information is derived from sources other than Armacell, Armacell is substantially, if not wholly, relying upon the other source(s) to provide accurate information. Information provided as a result of Armacell's own technical analysis and testing is accurate to the extent of our knowledge and ability, as of date of printing, using effective standardized methods and procedures. Each user of these products, or information, should perform their own tests to determine the safety, fitness and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. Since Armacell cannot control the end use of this product, Armacell does not guarantee that the user will obtain the same results as published in this document. The data and information are provided as a technical service and are subject to change without notice. * Microban antimicrobial product protection is limited to the product itself and is not designed to protect the users of these products from disease causing microorganisms, or as a substitute for normal cleaning and hygiene practices. Microban International, Ltd. makes neither direct nor implied health claims for the products containing Microban® antimicrobial product protection. Data, photomicrographs and information presented are based on standard laboratory tests and are provided for comparative purposes to substantiate antimicrobial activity for non-public health uses. Microban is a registered trademark of Microban International, Ltd.

AP Spiralflex	Duct Liner	Submittal	022	Eng/USA	5/2016
---------------	------------	-----------	-----	---------	--------