



# Technical Data Sheet

## Medium Tack Blue Duct Protection Film

---

### Product Description:

This product is a temporary protective mask designed for use on textured and rough surfaces. It is excellent for protection of plastics, textured metals, fiberglass and similar surfaces. It is also used as duct protection film and meets SMACNA guidelines. This product is available in clear and blue LDPE film with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup.

### Product Properties / Characteristics:

### Nominal Results

<b>Adhesion to Steel:</b> PSTC I (oz/in)	<b>3.0 to 7.0</b>
<b>Tack Level:</b>	<b>Medium</b>
<b>Tensile Strength:</b> PSTC 31 lb/sq in	<b>11</b>
<b>Elongation (%):</b> PSTC 31	<b>325</b>
<b>Thickness:</b> PSTC 33	<b>2 mils (nominal)</b>

---

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

**Limitations of Warranty:** Bay Insulation and seller warrants to customers that coated products constructed and delivered by Bay Insulation and seller to be free of defects in workmanship and to meet the specifications published by Bay Insulation which are available upon request. For a period of six (6) months from date of delivery and in the event of Bay Insulation brand product proved to be defective, the excluding solution, at Bay Insulation's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Bay Insulation.