

660/662

FIRE DOORS



INTEGRAL FRAME AND SILL FIRE-RATED COUNTER DOORS



COMMON APPLICATIONS INCLUDE SCHOOLS, CONCESSIONS, FOOD SERVICE COUNTERS, HOSPITALS AND CAFETERIAS

- **Built-in safety**
 - Fusible links separate at 165°F (74°C) for ambient conditions under 100°F (38°C), or at 212°F (100°C) for ambient conditions over 100°F (38°C), to close the door automatically under governor control
 - Meets strict fire safety testing standards
- **Options for added safety and simplified operation**
 - A variety of smoke detectors
 - Cylinder locking bottom bar with mortise cylinders
- **Optional Fire Sentinel® for fail-safe protection**
 - UL-listed, fail-safe device provides a 10-second time-delay release on alarm (up to 60 seconds optional) as allowed by Authority Having Jurisdiction
- **Choice of galvanized or stainless steel**



INDUSTRY LEADING
COMMERCIAL & INDUSTRIAL SOLUTIONS

MODELS 660/662 INTEGRAL FRAME AND SILL FIRE-RATED COUNTER DOORS

Standard features at a glance

Label	UL 1½-hour label
Maximum size	9'5" x 5'5" (2870 mm x 1651 mm)
Curtain	Model 660: Interlocking 22-gauge stainless steel slats Models 662: Interlocking 22-gauge galvanized steel slats
Integral frames/ guides	No. 4 finish stainless steel
Sill	14-gauge steel or stainless steel completely enclosed with fireproof acoustic filler
Hood	No. 4 finish stainless steel
Finish	Model 660: Stainless steel #4 brushed finish Model 662: Gray finish
Operation	Manual push-up
Mounting	Between jambs
Locking mechanism	Coil side padlockable slide locks



Fire Sentinel® time-delay release device



Smoke detectors




Smoke seals

Options

- Fire Sentinel® time-delay release device
- UL-listed brush-type smoke seals
- Photoelectric or ionization-type smoke detectors
- Locking mechanisms: Cylinder locking bottom bar with mortise cylinders
- Crank operation

Integral frame and sill slat data



Model	Opening	Width	Slat	Frame	Curtain	Sill
660	Thru 9'5"	(2870 mm)	22 gauge ss	Stainless steel	Stainless steel	Stainless steel
662	Thru 9'5"	(2870 mm)	22 gauge	Stainless steel	Galvanized steel	Stainless steel

Slats are galvanized and painted or stainless steel (ss).



INDUSTRY LEADING
COMMERCIAL & INDUSTRIAL SOLUTIONS



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067

1-800-929-DOOR • sales@overhaddoor.com

www.overhaddoor.com